


Natural Water Cycle
Lake of Constance, Germany: Swimming areas and potable water supply!
Optimizing sewage plants and starting stormwater management



www.klauswkoenig.com

Natural Water Cycle


Quality problems
from mixed sewer overflow into the lake



www.klauswkoenig.com

## Natural Water Cycle

Quantity Problems from stormwater runoff, if using only centralized structures:



- Damage by urban flooding
- Extreme changes in natural water cycle
- High cost for large dimensions of linear drainage and sewage structures
- No re-use of rainwater on site, no saving of potable water

www.klauswkoenig.com

# Stormwater management Dormitories at Salem College, Überlingen



- Planted roofs
- Infiltration swales

Positive effects: Evaporation, improving air quality Groundwater recharge

New: Architectural design

www.klauswkoenig.com

# Stormwater management Parking at Salem College, Überlingen




www.klauswkoenig.com

- Permeable surface
- open drains

Positive effects: Infiltration Evaporation

New: Landscape design

# Stormwater management Rainwater utilization in detached houses




www.klauswkoenig.com

### Applications:

- Irrigation
- Flushing toilets
- Laundry

## Stormwater management Rainwater utilization in detached houses



Substitution of potable water:

Max. 51 %

if the size of the roof and tank is big enough

German experience:

Per person min.

- •Roof 30 m<sup>2</sup>
- •Tank 1.5 m<sup>3</sup>

www.klauswkoenig.com

## Water Quality Filter




www.klauswkoenig.com

### German Vortex filter Patented system of cleaning

- Downpipe keeping full diameter
- Application for new and existing downpipes
- Long version to hide section with small pipe leading to the tank

# Water Quality Filter




www.klauswkoenig.com

### German Vortex filter


- •for downpipe and groundpipe
- •Different sizes
- •Plug in filter inlet
- •Worldwide availability

Water Quality
Improving by self processing sedimentation in water tanks



www.klauswkoenig.com

Water Quality
Improving by tank installation of calm inlet, floating suction, overflow syphon and sewer backflow prevention



www.klauswkoenig.com

Water Quality
German DIN states: no problem for laundry
if sedimentation and tank installation is in accordance with DIN 1989



www.klauswkoenig.com

## Regulations

By German national law mandatory in accordance with DIN 1989 and German water supply statutes:



www.klauswkoenig.com

1. Mains water backup only by free outlet

to ensure that the individual rainwater system cannot have an effect on the public water network

- 20 mm air gap
- No cross-connections

Regulations
By German national law mandatory
in accordance with DIN 1989 and German water supply statutes:



2. Labeling the rainwater distribution pipes

www.klauswkoenig.com

## Regulations

By German national law mandatory in accordance with DIN 1989 and German water supply statutes:



www.klauswkoenig.com

3.Labeling the rainwater serving valves

4.

The customer must notify the public health office and the water supplier prior to the installation



## Conclusion

Improving Rainwater Quality for re-use can be done by simple technology of

- •Filter
- Sedimentation
- •Calm Inlet
- Floating suction
- Overflow syphon
- Sewer backflow prevention

all inclusive in a tank in accordance with DIN 1989

Operation and maintenance are simple and easy, with low cost.

### Klaus W. König

## Thank you very much for your attention!

For more information in German, English, French see www.klauswkoenig.com

